



TECHNICAL DATA SHEET

D-FROST ICE MELTER

RECOMMENDATIONS

We recommend using this product on good quality, air-entrained concrete for cold weather climate.

UTILITY

Melts ice rapidly on contact on steps, sidewalks and driveways.

DIRECTIONS

Apply approximately at a rate of 50g per m² (11lb/100 sq.ft). Do not exceed 1 kg/10m² (2 lb/100 sq.ft). Remove slush and excess promptly after melting, to avoid the freeze/thaw cycles affecting the surface. Some poor quality surfaces may not withstand the stress associated with these cycles. Due to the irregularity and inconsistency of finish and porosity, the use of ice melter may present risks of surface spalling. Use of this product is done at user's risk.

PACKAGING

Available in 5 kg (11 lb).

STORAGE

Store in a closed container and keep away from other incompatible matters, in a dry area..

PRECAUTIONS : Keep out of reach of children. May cause slight eye irritations. Avoid contact with eyes.

FIRST AID TREATMENT : If in eyes, rinse the affected areas with water. If swallowed, drink water and call a doctor. Refer To Safety Data Sheet (SDS) for further information.

WARRANTY

Sable Marco's responsibility is limited to the replacement of the product. Further, Sable Marco Inc., has no control over the use or application of this product. Due to the irregularities and inconsistencies present on any concrete surface, the manufacturer or seller offers no warranty expressed or implied concerning the use of this product. User will assume all risk or loss following the application or use of this product. Proof of purchase will be required for all claims.

TECHNICAL INFORMATION

For further information, please contact :

Sable Marco Inc.

26 Chemin de la Pêche

Pont-Rouge, Québec, G3H 1C3, Canada

Tel. 418-873-4509 Fax. 418-873-2561

Toll free. 1-866-999-4509

<http://www.sablemarco.com/>